

Eddy Flow

The Cost Effective Replacement for Schedule 10

Realizing the growing need of fire protection systems in commercial and residential construction, Bull Moose Tube has added Eddy Flow to its comprehensive line of sprinkler pipe products.

Eddy Flow is a specially engineered replacement for schedule 10, offering better flow characteristics while providing design flexibility. This product is FM approved, as well as UL listed (for U.S. and Canada) for roll grooving and welding for use in fire protection

systems with a working pressure of 300 psi or less. Please check with appropriate sources for up-to-date listings and approval information.

As an added benefit, it is more economical to use than schedule 10 due to reduced delivery costs and ease of handling. Furthermore, Eddy Flow's larger ID provides an opportunity for downsizing and further cost savings.

COMPARISON

Nominal Pipe Size (in)	O.D. (in)	INSIDE DIAMETER			C.R.R.*	
		Eddy Flow (in)	Schedule 10 (in)	Schedule 40 (in)	Eddy Flow	Schedule 40
1 1/4	1.660	1.530	1.442	1.380	1.98	1.00
1 1/2	1.900	1.728	1.682	1.610	3.44	1.00
2	2.375	2.203	2.157	2.067	2.78	1.00
2 1/2	2.875	2.705	2.635	2.469	1.66	1.00
3	3.500	3.334	3.260	3.068	1.00	1.00
4	4.500	4.310	4.260	4.026	1.00	1.00

* Corrosion Resistance Ratio

BENEFITS

- **Dual Certified to ASTM A135 and A795.**
- **FM Approved for roll grooved, and welded, and plain-end application in wet systems.**
- **UL Listed (for U.S. and Canada) for joining by welding or by listed rubber gasketed fittings for use in wet, dry, preaction, and deluge type sprinkler systems.**
- **UL Listed (for US and Canada) and FM Approved for use with Victaulic® FIT® Fittings in plain end applications.**
- **Lightweight - saves shipping costs, and offers easier handling.**
- **Can be used with roll grooved couplings or welded outlets for pressures up to 300 psi.**
- **Floor stock available in various lengths produced in Casa Grande (AZ), Gerald (MO), and Masury (OH). Also can be ordered in custom lengths..**
- **Can be used for wet and dry* systems.**

* Eddy Flow can be hot dipped galvanized to meet FM's requirement for dry systems.

PIPE PREPARATION

For proper operation, all pipe surfaces should be cleaned prior to installation. In order to provide a leak-tight seat for the gasket, pipe surfaces should be free from indentations and projections from the end of the pipe to the groove. All loose paint, scale, dirt, chips, grease, and rust must be removed prior to installation. Failure to take these important steps may result in improper coupling assembly, causing leakage. Also, check the manufacturer's instructions for the specific fitting used.



Valvulas Industriales de Toluca S.A. de C.V.

Av. Emiliano Zapata, Esquina Altamiranos S/N,
Col. Emiliano Zapata, C.P. 52000,

Lerma Estado de México, Tel. (728) 284 7200

Fax (728) 282 2226 Nextel Ventas 52*107-42*76

vitventas@vitsa.com.mx

www.vitsa.com.mx